



Pos	Qty	Part No.	Description	Ordernumber
1	1	900024	Muffer BOS Oval120 Stainless Steel	<b>HO07N02-OVST - Stainless Steel</b>
1	1	900025	Muffer BOS Oval120 Carbon Steel	<b>HO07N02-OVCS - Carbon Steel</b>
		<b>80243</b>	<b>Mounting Parts:</b>	
2	1	72280	Link Pipe	<b>Weight:</b>
3	1	64655	Mounting Bracket	<b>Stock: 3,9 kg</b>
4	2	14049	Bolt M6x16	<b>Bos: 3,8 kg</b>
5	2	14087	Pull Spring 48 mm.	
6	1	64022	Clamp 40-43	<b>Noiselevel: @ 3125 rpm</b>
7	1	14060	Washer M8x24	<b>Stock: Specified 84,0 dB(A)</b>
				<b>Measured 81,7 dB(A)</b>
				<b>Bos: With DBeater 83,5 dB(A)</b>
				<b>Open 86,7 dB(A)</b>
				<b>Performance</b>
				<b>Stock: 43,4 Hp / 5345 rpm</b>
				<b>Bos: 45,1 Hp / 5419 rpm</b>
				<b>Max. Hp incr.: + 1,9 Hp / 5422 rpm</b>
				<b>Max Nm incr.: + 2,8 Nm / 2489 rpm</b>
<b>Extra Parts:</b>				
		50119	DBeater Ø32 Hyper	

### Tips

In order to avoid smudges and fingerprints burning into the surface it is imperative to clean the exhaust before starting the engine, burnt in stains are very difficult to remove.  
After 300 miles or 500 kms. check all nuts and bolts and retighten if necessary.