



**Approval Number**

\* Only for F800 series

**E 4** 2317 (9) TYPE 8004 \*

Pos	Qty	Part No.	Description	Ordernumber
1	1	900066	Muffler HyperFox Oval 120 S 180 Shot Blasted	<b>BM08F01-HFSB - Shot Blasted</b>
1	1	900020	Muffler HyperFox Oval 120 S 180 Carbon Steel	<b>BM08F01-HFCS - Carbon Steel</b>
1	1	900067	Muffler HyperFox Oval 120 S 180 Black Coated	<b>BM08F01-HFBC - Black Coated</b>
		<b>80003</b>	<b>Mounting Parts:</b>	
2	1	72182	Link Pipe	
3	1	64539	Mounting Bracket	
4	2	14049	Bolt M6x16	
5	1	14092	Rubber	
6	1	64621	Bushing	
7	1	14066	Bolt M8x25	
8	1	14060	Washer M8	
9	2	14087	Pull Spring 48 mm.	
10	1	64020	Clamp 57	
				<b>Weight:</b>
				Stock: 5,0 kg
				Bos: 3,5 kg
				<b>Noiselevel: @ 3500 rpm (F800 GS)</b>
				Stock: Specified 88,0 dB(A)
				Measured 87,6 dB(A)
				Bos: With DBeater 87,4 dB(A)
				Open 94,4 dB(A)
				<b>Performance (F800 GS)</b>
				Stock: 85,2 Hp / 7565 rpm
				Bos: 87,7 Hp / 7561 rpm
				Max. Hp incr.: + 3,9 Hp / 4837 rpm
				Max Nm incr.: + 5,6 Nm / 4820 rpm

**Extra Parts:**

650079 DBeater Ø32 Hyper Restriction

**Tips:**

In order to avoid smudges and fingerprints burning into the surface it is imperative to clean the exhaust before starting the engine, burnt in stains are very difficult to remove.  
After 300 miles or 500 kms. check all nuts and bolts and retighten if necessary.