



Approval Number



00048G TYPE 1025

Pos	Qty	Part No.	Description	Ordernumber
1	1	900120	Muffl. StreetFox Type 1025 Shot Blasted	KA09Z01-SFSB - Shot Blasted
1	1	900121	Muffl. StreetFox Type 1025 Black Coated	KA09Z01-SFBC - Black Coated
1	1	900122	Muffl. StreetFox Type 1025 Carbon Steel	KA09Z01-SFCS - Carbon Steel
		850041	Mounting Parts:	Weight:
2	1	750028	Adapter	Stock: 3,8 kg
3	1	700053	Mounting Bracket	Bos: 2,4 kg
4	4	14148	M6x16 Torx Flange Screw	Noiselevel: @ 4750 rpm
5	2	300032	Pull Spring 25 mm.	Stock: Specified 91,0 dB(A)
6	1	64020	Clamp 57	Measured 88,5 dB(A)
7	1	700052	Heatshield Z900	Bos: Measured 90,0 dB(A)

Performance

Stock: 130,5 Hp / 9418 rpm
 Bos: 136,1 Hp / 9596 rpm
 Max. Hp incr.: + 5,6 Hp / 9596 rpm
 Max Nm incr.: + 4,9 Nm / 7393 rpm

Tips

In order to avoid smudges and fingerprints burning into the surface it is imperative to clean the exhaust before starting the engine, burnt in stains are very difficult to remove.
 After 300 miles or 500 kms. check all nuts and bolts and retighten if necessary.

Extra Parts: